



## APP Modified Bitumen Membranes

<b>Product</b>	<b>Use</b>	<b>Description</b>	<b>Size</b>	<b>Standard</b>
APPeX® 4.5M	Cap	A polyester-reinforced, mineral-surfaced, APP modified bitumen cap sheet.	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM D 6222, Type I, Grade G
APPeX® 4.5M FR	Cap	A fire-retardant, polyester reinforced, mineral-surfaced, APP modified bitumen cap sheet.	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM D 6222, Type I, Grade G
APPeX® 4S	Cap	A polyester-reinforced, smooth-surfaced, APP modified bitumen cap sheet.	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM D 6222, Type I, Grade S
BICOR™ M FR	Cap	A fire-retardant, fiber glass- and polyester-reinforced, mineral-surfaced, APP modified bitumen cap sheet.	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM 6223, Type II, Grade G
BICOR™ S	Cap/Ply	A premium, fiber glass- and polyester-reinforced, smooth-surfaced, APP modified bitumen cap sheet (special order product).	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM 6223, Type II, Grade S
JM APP™ Base	Base/Ply	A fiber glass-reinforced, smooth-surfaced, APP modified bitumen base sheet.	150 ft <sup>2</sup> (13.94 m <sup>2</sup> )	ASTM 6509
TRICOR™ M FR	Cap	A premium, fire-retardant, fiber glass- and polyester-reinforced, mineral-surfaced, APP modified bitumen cap sheet (special order product).	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM 6223, Type II, Grade G
TRICOR™ S	Cap/Ply	A premium, fiber glass- and polyester-reinforced, smooth-surfaced, APP modified bitumen cap sheet (special order product).	100 ft <sup>2</sup> (9.29 m <sup>2</sup> )	ASTM 6223, Type II, Grade S