



# Asphalt Primer

## Description

**Johns Manville Asphalt Primer** is a specification grade, penetrating priming solution of selected asphalt base in petroleum solvent. This primer meets specification ASTM D 41 for asphalt primers for commercial roofing, dampproofing and waterproofing.

## Use

Asphalt Primer is used to prepare substrates prior to the application of hot asphalt or cold adhesives in BUR, SBS and APP modified bitumen roofing systems. Substrates include concrete, gypsum, masonry, block, brick, and metal surfaces. Do not use Asphalt Primer as a finish coat on roofs. **For professional use only.**

## Surface Preparation

All surfaces must be swept clean and free from oil, grease, rust, scale, loose paint and dirt.

## Application

Stir in the container before applying. Apply using a brush or commercial grade spray equipment. **Do not thin.**

## Clean-Up

All equipment can be cleaned with mineral spirits. Use care when handling solvents. Clean hands with waterless hand cleaner.

## Coverage

Coverage is approximately ½ to 1 gal/100 ft<sup>2</sup> (0.41 to 0.61 l/m<sup>2</sup>). Application rate varies according to the type, age and condition of the surface.



## Advantages

- Low VOC
- Good for hot asphalt or cold adhesive applications
- Sprayable

## Packaging

4.75 gal (17.9 l) pails

## Shelf Life

Two years from date of manufacture

## Specifications

- ASTM D41, Type II
- SS-A-701 Federal Specification
- AASHTO M-116

## Typical Physical Properties

Flash Point..... 104°F (40°C)  
VOC..... <350 g/L max., calculated

## Caution

COMBUSTIBLE MATERIAL • SHIP AND STORE AWAY FROM OPEN FLAMES, HEAT OR SOURCES OF IGNITION • KEEP ALL PAILS TIGHTLY SEALED WHILE IN STORAGE • USE ONLY IN WELL VENTILATED AREAS • MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION • HARMFUL OR FATAL IF SWALLOWED • AVOID CONTACT WITH SKIN • USE IMPERVIOUS CLOTHING AND RUBBER GLOVES TO AVOID PROLONGED OR REPEATED CONTACT WITH SKIN • READ THE CONTAINER LABEL AND FOLLOW ALL SAFETY INSTRUCTIONS.

Refer to the Material Safety Data Sheet and product label prior to using this product.