

Zeston® 300 Series PVC Fitting Covers and Jacketing

For Tees, Valves, 45° Elbows and Short Radius 90° Elbows

Selection Chart

Copper Tubing Size	Pipe Insulation Thickness — in. (mm)								
	in. (mm)	1/2 (13)	1 (25)	1 1/2 (38)	2 (51)	2 1/2 (64)	3 (76)	3 1/2 (89)	4 (102)
1/2	13	2.0	2.5	3.5	4.5	5.5	6.5	—	—
5/8	16	2.0	3.0	3.5	4.5	5.5	6.5	7.5	8.5
7/8	22	2.0	3.0	4.0	5.0	6.0	7.5	8.5	9.5
1 1/8	29	2.0	3.0	4.0	5.0	6.5	7.5	8.5	9.5
1 3/8	35	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5
1 5/8	41	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5
2 1/8	54	3.0	4.0	5.0	6.0	7.5	8.5	9.5	10.5
2 5/8	67	3.5	4.5	5.5	6.5	7.5	8.5	9.5	10.5
3 1/8	79	4.0	5.0	6.5	7.5	8.5	9.5	10.5	11.5
3 5/8	92	5.0	5.5	6.5	7.5	8.5	9.5	10.5	11.5
4 1/8	105	5.5	6.5	7.5	8.5	9.5	10.5	11.5	12.5
5 1/8	130	6.5	7.5	8.5	9.5	10.5	11.5	12.5	14.0
6 1/8	156	7.5	8.5	9.5	10.5	11.5	12.5	14.0	15.0

Zeston 300 PVC insulated fitting covers are sized to fit Micro-Lok® fiber glass pipe insulation and all other types of pipe insulation manufactured in accordance with ASTM C 585.



Johns Manville

Performance Materials Division

P.O. Box 5108

Denver, CO 80217-5108

www.jmpipeinsulation.com

Copyright © 2006 Johns Manville
Printed in USA

CI-109 9-06 (Replaces 11-01)

Zeston® 300 Series PVC Fitting Covers and Jacketing

Iron Pipe Size	Pipe Insulation Thickness — in. (mm)								
	in. (mm)	1/2 (13)	1 (25)	1 1/2 (38)	2 (51)	2 1/2 (64)	3 (76)	3 1/2 (89)	4 (102)
3/8	10	2.0	3.0	3.5	—	—	—	—	—
1/2	13	2.0	3.0	4.0	5.0	6.5	7.5	8.5	9.5
3/4	19	2.0	3.0	4.0	5.0	6.5	7.5	8.5	9.5
1	25	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5
1 1/4	32	3.0	3.5	5.0	5.5	6.5	7.5	9.5	10.5
1 1/2	38	3.0	4.0	5.0	6.5	7.5	8.5	9.5	10.5
2	51	3.5	4.5	5.5	6.5	7.5	8.5	9.5	10.5
2 1/2	64	4.0	5.0	6.5	7.5	8.5	9.5	10.5	11.5
3	76	4.5	5.5	6.5	7.5	8.5	9.5	10.5	11.5
3 1/2	89	5.0	6.5	7.5	8.5	9.5	10.5	11.5	12.5
4	102	5.5	6.5	7.5	8.5	9.5	10.5	11.5	12.5
4 1/2	114	6.0	7.5	8.5	9.5	10.5	11.5	12.5	14.0
5	127	6.5	7.5	8.5	9.5	10.5	11.5	12.5	14.0
6	152	7.5	8.5	9.5	10.5	11.5	12.5	14.0	15.0
7	178	8.5	9.5	10.5	11.5	12.5	14.0	15.0	16.0
8	203	9.5	10.5	11.5	12.5	14.0	15.0	16.0	17.0
9	229	10.5	11.5	12.5	14.0	15.0	16.0	17.0	18.0
10	254	11.5	12.5	14.0	15.0	16.0	17.0	18.0	19.0
11	279	12.5	14.0	15.0	16.0	17.0	18.0	19.0	20.0
12	305	14.0	15.0	16.0	17.0	18.0	19.0	20.0	21.0
14	356	15.0	16.0	17.0	18.0	19.0	20.0	21.0	22.0
15	381	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0
16	406	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0
17	432	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0
18	457	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0
19	483	20.0	21.0	22.0	23.0	24.0	25.0	26.0	27.0
20	508	21.0	22.0	23.0	24.0	25.0	26.0	27.0	28.0

Zeston 300 PVC insulated fitting covers are sized to fit Micro-Lok® fiber glass pipe insulation and all other types of pipe insulation manufactured in accordance with ASTM C 585.