



## Coatings

<b>Product</b>	<b>Use</b>	<b>Description</b>	<b>Size</b>	<b>Standard</b>
Fibrated Aluminum Roof Coating	Weather-proofing Coating	Cut-back, asphalt-based, non-asbestos, fiber-reinforced, highly reflective aluminum coating for use on smooth-surfaced roof.	5 gal (18.9 l) can	ASTM D 2824, Type III
TopGard® Type A	Reflective Coating	A brush grade, non-asbestos coating consisting of aluminum flakes suspended in an emulsified asphalt, for use on smooth-surfaced roof.	5 gal (18.9 l) can	ASTM D 6848, Type IV
TopGard® Type B	Weather-proofing Coating	Clay-stabilized, water-based asphalt emulsion, with non-asbestos reinforcing fibers, for use on smooth-surfaced roof.	5 gal (18.9 l) can 55 gal (208.2 l) drum	ASTM D 1227, Type II
TopGard® Base Coat	Bleed-blocking Coating	A 100% acrylic elastomeric coating engineered for superior adhesion to BUR, smooth and/or mineral-surfaced bitumen roofing products.	5 gal (18.9 l) can 55 gal (208.2 l) drum 275 gal (1,041 l) tote	ASTM D 6083
TopGard® 5000	Reflective Coating	A 100% acrylic elastomeric coating applied over TopGard Base. It is especially effective in colder climates where extra levels of low temperature flexibility are required.	5 gal (18.9 l) can 55 gal (208.2 l) drum 275 gal (1,041 l) tote	ASTM D 6083
TopGard® 4000	Reflective Coating	A multipurpose, 100% acrylic elastomeric coating for use over a variety of substrates, including asphalt single-ply and metal roofing	5 gal (18.9 l) can 55 gal (208.2 l) drum 275 gal (1,041 l) tote	ASTM D 6083