



JM EPDM Roofing Systems Guarantee/Spec Matrix

System	Term	System Type	Membrane	Spec	Insulation Substrate	Notes
BEST	20 year NDL	Fully Adhered	JM EPDM 90 FR or JM EPDM 60 FR	SE9A SE6A	<u>One Layer:</u> WF, I, E, TE OR <u>Two Layers:</u> (Choose 1, each layer) Top: WF, I, E, TE, DD Bottom: E, TE	<ol style="list-style-type: none"> 20-year Guarantees available for new construction, or complete tear-off. Re-covers allowed only with a full, non-destructive moisture survey with conforming core cuts. All wet materials must be removed and replaced with new materials or removal of existing roof cover. New construction or complete tear-off only. Field laps must have a minimum 3" (80 mm) JM Peel & Stick Seam Tape and stripped in with 6" (150 mm) JM Peel & Stick Sealing Strip or 6" (150 mm) JM Peel & Stick Seam Tape. Refer to specifications for specific system requirements.
			JM EPDM 60 R	SE6RA		
		Mechanically Fastened	JM EPDM 60 R	SE6RM		
BETTER	15 year NDL	Fully Adhered	JM EPDM 90 FR or JM EPDM 60FR	SE9A SE6A	<u>One Layer:</u> WF, I, E, TE, DD* OR <u>Two Layers:</u> (Choose 1, each layer) Top: WF, I, E, TE, DD Bottom: E, TE	<ol style="list-style-type: none"> Retrofit installations require that blisters, buckles and ridges shall be cut and patched to provide a reasonably level substrate surface. Insulation must be JM (except DD). 15-year Guarantees require the use of a minimum 3" (80 mm) JM EPDM Seam Tape. Refer to specifications for specific system requirements.
			JM EPDM 60 R or JM EPDM 45 R	SE6RA SE4RA		
		Mechanically Fastened	JM EPDM 60 R or JM EPDM 45 R	SE6RM SE4RM		
		Ballasted	JM EPDM 90 FR or JM EPDM 60 FR	SE9B SE6B		
			JM EPDM 60 R or JM EPDM 45 R	SE6RB SE4RB		
GOOD	5 or 10 year NDL	Fully Adhered	JM EPDM 90 FR, JM EPDM 60 FR or JM EPDM 45 FR	SE9A SE6A SE4A	None (Slip sheet–Re-cover only) OR <u>One Layer:</u> WF, I, E, TE, DD* OR <u>Two Layers:</u> (Choose 1, each layer) Top: WF, I, E, TE, DD Bottom: E, TE	<ol style="list-style-type: none"> Retrofit installations require that blisters, buckles and ridges shall be cut and patched to provide a reasonably level substrate surface. Refer to specifications for specific system requirements. Insulation must be JM (except DD). 10-year Guarantees require the use of a minimum 3" (80 mm) JM EPDM Seam Tape.
			JM EPDM 60 R or JM EPDM 45 R	SE6RA SE4RA		
		Mechanically Fastened	JM EPDM 60 R or JM EPDM 45 R	SE6RM SE4RM		
		Ballasted	JM EPDM 90 FR or JM EPDM 60 FR	SE9B SE6B		
			JM EPDM 60 R or JM EPDM 45 R	SE6RB SE4RB		

Insulation and Cover Boards

WF = Wood Fiber

I = Invinsa Roof Board

DD = DensDeck®

E = ENRGY 3/ISO 3

TE = Tapered ENRGY 3/Tapered ISO 3

* Summit and Pinnacle Peak Advantage Contractors only.

Refer to the JM Single Ply Guarantee Charges and Requirements pages for more information on 25 and 30 year options. Contact Technical Services, your local JM sales representative or the Web for more information.

DensDeck is a registered trademark of Georgia-Pacific, LLC.