

# JM EPDM Membrane Selector Guide

RS-8901 6-10 (Replaces 6-08)

Description	Product	ASTM	Thickness	Color	Sizes Width x Length	Area per Roll	Weight	Specifications			Guarantees		
								Mechanically Fastened	Fully Adhered	Ballasted	Mechanically Fastened	Fully Adhered	Ballasted
Nonreinforced, fire rated EPDM for use in fully adhered and ballasted systems. For use as a flashing in some applications	JM EPDM 45 FR		45 mil		10' x 50' (3.05 m x 15.24 m)	500 ft (46.45 m)	179 lb (81.23 kg)	N/A	SE4A-(T)	SE4B-(T)	N/A	5 or 10 yr NDL	5 or 10 yr NDL
					10' x 100' (3.05 m x 30.48 m)	1,000 ft (92.90 m)	335 lb (151.75 kg)						
					20' x 50' (6.1 m x 15.24 m)	1,000 ft (92.90 m)	335 lb (151.75 kg)						
					20' x 100' (6.1 m x 30.48 m)	2,000 ft (185.81 m)	659 lb (299.11 kg)						
					30' x 100' (9.14 m x 30.48 m)	3,000 ft (278.71 m)	970 lb (440.16 kg)						
					40' x 100' (12.19 m x 30.48 m)	4,000 ft (371.61 m)	1,281 lb (581.22 kg)						
	JM EPDM 60 FR		60 mil		10' x 50' (3.05 m x 15.24 m)	500 ft (46.45 m)	231 lb (104.74 kg)	N/A	SE6A-(T)	SE6B-(T)	N/A	5, 10, 15, or 20 yr NDL	5, 10, or 15 yr NDL
					10' x 100' (3.05 m x 30.48 m)	1,000 ft (92.90 m)	438 lb (198.77 kg)						
					15' x 100' (4.57 m x 30.48 m)*	1,500 ft (139.35 m)	677 lb (307.11 kg)						
					20' x 50' (6.1 m x 15.24 m)	1,000 ft (92.90 m)	438 lb (198.77 kg)						
					20' x 100' (6.1 m x 30.48 m)	2,000 ft (185.81 m)	867 lb (393.14 kg)						
					30' x 100' (9.14 m x 30.48 m)	3,000 ft (278.71 m)	1,281 lb (581.22 kg)						
	JM EPDM 90 FR		90 mil		10' x 100' (3.05 m x 30.48 m)	1,000 ft (92.90 m)	625 lb (283.65 kg)	N/A	SE9A-(T)	SE9B-(T)	N/A	5, 10, 15, or 20 yr NDL	5, 10, or 15 yr NDL



\* No Fold