

# JM EPDM Membrane Selector Guide

Description	Product	ASTM	Thickness	Color	Sizes Width x Length	Area per Roll	Weight	Specifications			Guarantees		
								Mechanically Fastened	Fully Adhered	Ballasted	Mechanically Fastened	Fully Adhered	Ballasted
Polyester reinforced, factory cleaned EPDM for use in ballasted, mechanically fastened, and fully adhered roofing systems.	JM EPDM 45R	D 4637	45 mil	Black	10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	300 lb (136.08 kg)	SE4RM-(T)	SE4RA-(T)	SE4RB-(T)	5, 10, or 15 yr NDL	5, 10, or 15 yr NDL	5, 10, or 15 yr NDL
	JM EPDM 60R		60 mil		7' x 100' (2.13 m x 30.48 m)	700 ft <sup>2</sup> (65.06 m <sup>2</sup> )	276.5 lb (125.42 kg)	SE6RM-(T)	SE6RA-(T)	SE6RB-(T)	5, 10, or 15 yr NDL	5, 10, 15, or 20 yr NDL	5, 10, or 15 yr NDL
			10' x 100' (3.05 m x 30.48 m)		1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	395 lb (179.17 kg)							
Nonreinforced, fire rated EPDM for use in fully adhered and ballasted systems. For use as a flashing in some applications	JM EPDM 45 FR	D 4637	45 mil	Black	10' x 50' (3.05 m x 15.24 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	179 lb (81.23 kg)	N/A	SE4A-(T)	SE4B-(T)	N/A	5 or 10 yr NDL	5 or 10 yr NDL
					10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	335 lb (151.75 kg)						
					20' x 50' (6.1 m x 15.24 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	335 lb (151.75 kg)						
					20' x 100' (6.1 m x 30.48 m)	2,000 ft <sup>2</sup> (185.81 m <sup>2</sup> )	659 lb (299.11 kg)						
					30' x 100' (9.14 m x 30.48 m)	3,000 ft <sup>2</sup> (278.71 m <sup>2</sup> )	970 lb (440.16 kg)						
					40' x 100' (12.19 m x 30.48 m)	4,000 ft <sup>2</sup> (371.61 m <sup>2</sup> )	1,281 lb (581.22 kg)						
	JM EPDM 60 FR	D 4637	60 mil	Black	10' x 50' (3.05 m x 15.24 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	231 lb (104.74 kg)	N/A	SE6A-(T)	SE6B-(T)	N/A	5, 10, 15, or 20 yr NDL	5, 10, or 15 yr NDL
					10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	438 lb (198.77 kg)						
					15' x 100' (4.57 m x 30.48 m)*	1,500 ft <sup>2</sup> (139.35 m <sup>2</sup> )	677 lb (307.11 kg)						
					20' x 50' (6.1 m x 15.24 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	438 lb (198.77 kg)						
					20' x 100' (6.1 m x 30.48 m)	2,000 ft <sup>2</sup> (185.81 m <sup>2</sup> )	867 lb (393.14 kg)						
					30' x 100' (9.14 m x 30.48 m)	3,000 ft <sup>2</sup> (278.71 m <sup>2</sup> )	1281 lb (581.22 kg)						
					10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	625 lb (283.65 kg)						
JM EPDM 90 FR	D 4637	90 mil	Black	10' x 100' (3.05 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	625 lb (283.65 kg)	N/A	SE9A-(T)	SE9B-(T)	N/A	5, 10, 15, or 20 yr NDL	5, 10, or 15 yr NDL	

\* No Fold