

Description

Extra High Load Fasteners are #21 fasteners with a #3 Phillips head. The point is designed for quick installation in new and re-roof applications. Extra High Load Fasteners are only compatible with Extra High Load Plates.

The Extra High Load Plate is a 3" (7.62 cm) diameter, Galvalume-coated steel plate with eye hooks. The Extra High Load Plate incorporates an oversized diameter hole to accommodate the larger wire size of the Extra High Load Fastener.

Use

Use to attach membrane in the field of the roof to 18 - 26 (gauge (1.2 mm - 0.5 mm) metal, or wood decks.

Advantages

- Oversized heavy shank and thread diameters for enhanced pullout resistance in light gauge steel and aluminum roof decks.
- Deep buttress threads further increase pullout resistance.
- Miniature drill point penetrates decks quickly and contributes to exceptional resistance to backout as well as pull out.
- Exceeds the corrosion resistance standards of FM Global Approval Standard #4470.



Sizes and Packaging

Fastener: 2" to 3" (5.1 cm to 7.6 cm), 1,000/pail
4" to 6" (10.2 cm to 15.2 cm), 500/pail
7" to 8" (17.8 cm to 20.32 cm), 250/pail
A bit is provided in each pail.

Plates: 3" (7.6 cm) round, 500/pail

Precautions

Refer to the Material Safety Data Sheet prior to using Extra High Load Fasteners and Plates. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.

*Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.