

Product	Description	Attachment*			System(s) [†]		Deck	Size	Color	Pkg
		In	Ba	Me	SP	Bit				
UltraFast® Fastener	#12 case-hardened steel, polymer-coated fastener. Available in ¼" (6 mm) hex or #3 Phillips head. Compatible with UltraFast Metal Round or Square plates and Ultra-Fast Plastic Locking Plate.	x			x	x	Metal (18 to 26 ga.), Wood	1½" to 8" (41 mm to 203 mm)	Blue	1,000/pail (1) #3 Phillips bit/pail (1) ¼" (6 mm) hex head bit/3 pails
UltraFast® Plate (Metal)	Recessed round or square flat-bottomed plate. Compatible with UltraFast and All Purpose Fasteners.	x			x	x		3" (76 mm) round or square		1,000/pail
UltraFast® Plate (Locking Plastic)	High strength polypropylene plates with a special locking feature. Compatible with UltraFast and All Purpose Fasteners.	x			x	x		3" (76 mm) round	Blue	1,000/box
UltraFast Pre-Assembled Fasteners with Plates	Pre-assembled fastener and plate. #12 case-hardened, polymer-coated steel. #3 Phillips head or ¼" (6 mm) hex head (special order only). Metal recessed round plate or round plastic locking plate.	x			x	x	Metal (18 to 26 ga.), Wood	Fastener: 2 ¼" to 8" (57 mm to 203 mm) Plate: 3" (76 mm) round	Blue (Fastener only)	Quantities vary by fastener length. Bit provided in each box.
UltraFast® AccuTrac™ Fastener and Plate System	AccuTrac tool positions UltraFast Fastener and UltraFast AccuTrac metal plate in a one-step process. UltraFast AccuTrac Plates are specifically designed for use with the AccuTrac tool. Plates are available in flat-bottom or recessed designs. Standard UltraFast plates are not compatible with the AccuTrac Tool.	x			x	x	Metal (18 to 26 ga.)	Fastener: 1½" to 6" (41 mm to 152 mm) lengths Plate: 3" (76 mm) square	Blue (Fastener only)	Fasteners and Plates purchased separately.
Heavy Duty Low Profile Plate	Square Galvalume®-coated plate with flat surface. Designed for use where flat plates are desired to increase performance or aesthetics. Compatible with UltraFast and All Purpose Fasteners. Please contact your JM sales representative for information regarding this product.	x			x		N/A	2 ¾" (70 mm) square		1,000/pail
UltraLok™ Locking Impact Fastener	Pre-assembled Galvalume-coated steel tube and disc with a high-tensile steel wire locking staple.	x	x		x	x	Cementious Wood Fiber, Lightweight Concrete, Gypsum	Fastener: 1.4" to 4.8" (36 mm to 122 mm) lengths Plate: 2.7" (69 mm)		1.4" to 3.8" - 500/carton 4.8" - 250/ carton
Lightweight Concrete Base Sheet Pre-Assembled Fastener and Plate	Pre-assembled fastener and plate. Twin-legged, expanding fastener with Galvalume-coated steel plate.		x		x	x	Lightweight Concrete, Gypsum	Fastener: 1.2" (31 mm) and 1.7" (43 mm) lengths Plate: 2.7" (69 mm) round	Black	1.2" - 1,000/box 1.7" - 500/box
Polymer Auger - Fastener with Plates	Glass-reinforced, nylon fastener with an internal ¼" (6 mm) square drive and 1" (25 mm) diameter head. Each fastener comes with either a 2" (51 mm) barbed-plate design to grip membrane or a 3" (76 mm) square plate designed to lock onto Polymer Auger fastener head. Not pre-assembled.	x		x	x	x	Cementious Wood Fiber, Gypsum	Fastener: 2½" to 7½" lengths Plate: 2" (51 mm) round and 3" (76 mm) square	Black	Fastener: 500/box Plate: 1,000/pail

* Attachment: In = Insulation; Ba = Base Sheet; Me = Membrane

† System(s): SP = Single Ply; Bit = Bituminous



Fasteners and Plates

Product	Description	Attachment*			System(s) [†]		Deck	Size	Color	Pkg
		In	Ba	Me	SP	Bit				
APB Plate	Galvalume-coated steel, barbed plate. Provides an even distribution of loads and eliminates sharp corners that can damage the insulation or membrane. Designed for use in mechanically fastened single ply systems. Compatible with All Purpose and High Load Fasteners. Please contact your JM sales representative for information regarding this product.	x		x	x			2" (51 mm) round		1,000/pail
All Purpose Fastener	#14 case-hardened steel fastener with a #3 Phillips head. Compatible with UltraFast metal (round or square) or plastic locking (round) plates.	x		x	x		Metal (18 to 26 ga.), Wood	1¼" (32 mm), 2" to 24" (51 mm to 610 mm) lengths	Grey	Quantities vary by fastener length. Bit provided in each plastic pail.
Structural Concrete Deck Fasteners	#14, knurled-thread, hammer-in, flat-head fastener with a premium coating. Compatible with UltraFast round, flat-bottomed metal plates.	x		x	x	x	Structural Concrete	2" to 10" (51 mm to 254 mm) lengths	Black	2"-8" - 500/pail 9"-10" - 250/pail
JM PVC or JM TPO RhinoPlate®	Specially-coated plate with a recessed center and raised, flat bonding surface. Compatible with High Load and All Purpose Fasteners	x		x	x			3" (76 mm) round	PVC: Black TPO: Amber	500/pail
Membrane Battens	Pre-punched, polymer batten strips and pre-punched, countersunk anchor bar.			x	x			Batten Strip: 1" x 250' (25 mm x 76.2 m) Anchor Bar: 1" x 10' (25 mm x 30.5 m)		250'/tube 500'/tube
JM Purlin Fastener	Case-hardened steel, polymer-coated fastener; available in ¼" (6 mm) hex head. Compatible with UltraFast (metal or plastic) locking plates and High Load Plates.			x	x		Structural Steel	3¾" to 8" (95 mm to 203 mm) lengths		500/pail
Lite-Deck Fastener and Plates	Square-drive, course-thread fastener, Galvalume-coated steel plates. Pre-drilling required. Not pre-assembled. Please contact your JM sales representative for information regarding this product.			x	x		Cementious Wood Fiber, Lightweight Concrete, Gypsum	Fastener: 2 5/8" to 12" (67 mm to 305 mm) lengths Plate: 3" (76 mm) round		2½" to 4" - 500/pail 5" to 8" - 250/pail 9" to 12" - 125/pail Plate: 500/pail
Zinc Nail-In Anchor	Zinc-plated steel pin. Designed to attach termination bar. Pre-drilling required. Please contact your JM sales representative for information regarding this product.			x	x	x	Concrete wall, Masonry wall	¼" (6 mm) dia., 1¼" (32 mm) length		1,000/pail
Anchor Disc	Round plate used for single ply membrane termination. Compatible with All Purpose and High Load Fasteners. <i>No data sheet is currently available.</i> Please contact your JM sales representative for information regarding this product.			x	x	x		2" (51 mm) round		1,000/pail

* Attachment: In = Insulation; Ba = Base Sheet; Me = Membrane

[†] System(s): SP = Single Ply; Bit = Bituminous



Fasteners and Plates

Product	Description	Attachment*			System(s) [†]		Deck	Size	Color	Pkg
		In	Ba	Me	SP	Bit				
High Load Fasteners	#15 fastener with a #3 Phillips head. Compatible with High Load, APB, Anchor Disc, and RhinoPlate. For use in the High Load Reel-Fast Plate System and High Load AccuSeam Plate System.			x	x	x	Metal (18 to 26 ga.), Wood	1¼" (32 mm), 2" to 24" (51 mm to 610 mm) lengths	Blue	Quantities vary by fastener length.
High Load Plates	20-gauge (0.9 mm) Galvalume-coated steel discs with eye hooks. Compatible with High Load Fasteners			x	x	x	Metal (18 to 26 ga.), Wood	2⅝" (60 mm) round		1,000/pail
High Load Pre-Assembled Fasteners and Plates	Pre-assembled fastener and plate. #15 fasteners with a #3 Phillips head. 20-gauge (0.9 mm) Galvalume-coated steel disc with eye hooks.			x	x	x	Metal (18 to 26 ga.), Wood	Fastener: 2" to 8" (51 mm to 203 mm) lengths Plates: 2⅝" (60 mm) round	Blue	Quantities vary by fastener length. Bit provided in each plastic pail.
Extra High Load Fasteners and Plate	#21 fastener with a #3 Phillips head. Galvalume-coated, 20-gauge (0.9 mm) steel plate with eye hooks. Not pre-assembled.			x	x		Metal (18 to 26 ga.), Wood	Fastener: 2" to 8" (51 mm to 203 mm) lengths Plates: 3" (76 mm) round	Blue (Fastener only)	Fastener: Quantities vary by fastener length. Bit provided in each plastic pail. Plate: 500/pail.
JM Termination Systems	Roll-formed, pre-punched aluminum strips with round, Galvalume-coated steel discs, galvanized anchors and polymer-coated fasteners.			x	x	x	Metal (18 to 26 ga.)	Termination Bar: 1.35" x 10' (34 mm x 3.05 m) strips Anchor Disc: 2" (51 mm) diameter Fastener: 1¼" (32 mm)		Termination Bar: 500/tube Anchor Disc: 1,000/box Fastener: 1,000/pail
High Load AccuSeam™ Plate System	Premier, automated system for mechanically fastened seams. The system positions a High Load AccuSeam Plate and installs a High Load Fastener in a one-step, continuous process. Ensures a 6" (152 mm) and 12" (305 mm) o.c. placement. Standard High Load Plates are not compatible with the AccuSeam Tool.			x	x		Metal (18 to 26 ga.), Wood	Fastener: Up to 6" (152 mm) Plate: 2⅝" (60 mm) round	Blue (Fastener only)	18 sleeves of stacked plates 1,000 plates/pail
High Load Reel-Fast™ Plate System	Galvalume-coated, High Load Plates heat-sealed onto a plastic strip. Plates are pre-spaced 6" (152 mm) and 12" (305 mm) o.c. Compatible with High Load Fasteners.			x	x		Metal (18 to 26 ga.), Wood	2⅝" (60 mm) round	Blue (Fastener only)	500 plates/reel 2 reels/box

* Attachment: In = Insulation; Ba = Base Sheet; Me = Membrane

[†] System(s): SP = Single Ply; Bit = Bituminous