

Description

The High Load AccuSeam System is a premier automated system for mechanically attached seams. The System positions the 2³/₈" (6.03 cm), round, High Load Plate with eye hooks, and installs the High Load Fastener, up to 6" (15.24 cm) in length in a one-step, continuous process. Standard High Load Plates are not compatible with the AccuSeam Fastener and Plate System.

The unique tail on the AccuSeam tool, ensures a 6" (15.24 cm) or 12" (30.48 cm) o.c. placement.

Use

Designed for mechanical attachment of TPO, PVC and EPDM single ply membrane to steel and wood roof decks.

Advantages

- Accurately spaces seam fasteners on either 6" (15.24 cm) or 12" (30.48 cm) centers.
- Depth of drive adjustment eliminates overdriving and underdriving.
- Consistent vertical alignment of fasteners ensures maximum thread engagement and pull-out performance.
- One person can do the work of two, in a standup operation that reduces operator fatigue.
- Dramatically increases productivity and accuracy.



Sizes and Packaging

The High Load AccuSeam Plate is packaged specifically for use with the AccuSeam automated system.

Fastener: 1¹/₄", 2" to 5" (3.2 cm, 5.1 to 12.7 cm), 1,000/pail
6" to 14" (15.2 to 35.6), 500/pail
16" to 24" (40.6 cm to 61 cm), 250/pail

Plates: 18 sleeves of stacked plates
1,000 plates per bucket.

Note: To be ordered with the blue High Load Fastener.

Precautions

Refer to the Material Safety Data Sheet prior to using High Load AccuSeam Fastener and Plate System. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.