

Description

The High Load Fastener is a blue, corrosion-resistant #15 fastener with a #3 Phillips head. The point is designed for quick installation in new or re-roof applications.

High Load Plates are heavy duty, 2 $\frac{3}{8}$ " (6.03 cm) round, 20-gauge (0.9 mm) Galvalume-coated steel seam plates with eye hooks.

Use

Use to attach membranes in the field of the roof to 18 - 26 gauge (1.2 mm - 0.5 mm) metal, or wood decks. The screw and plate system provides positive attachment and resistance to uplift forces.

High Load Fasteners and Plates are approved for use with any Peak Advantage® Guarantee.

Advantages

High Load Fasteners:

- Heavy-duty construction for enhanced holding power
- Deep #3 Phillips head recess permits positive bit engagement
- Corrosion-resistant coating, exceeding FM Global® Approval Standard #4470 corrosion requirements.

High Load Plates:

- Rigid, corrosion-resistant metal
- Low in-seam profile
- Heavy-duty construction for enhanced FM Global approvals



Sizes and Packaging

Fastener: 1 $\frac{1}{4}$ ", 2" to 5" (3.2 cm, 5.1 to 12.7 cm), 1,000/pail
6" to 14" (15.2 to 35.6), 500/pail
16" to 20" (40.6 cm to 50.8 cm), 250/pail
22" (55.9 cm) and 24" (61 cm), 125/box

Plate: 2 $\frac{3}{8}$ " (6.03 cm) round, 1,000/pail

Precautions

Refer to the Material Safety Data Sheet prior to using High Load Fasteners and Plates. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.

*Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.