

# Invinsa® Roof Board

## Underwriters Laboratories Code Approvals

### JM Single Ply Systems - Fully Adhered

Membrane	Deck	Class	Slope	Insulation	Cover Board
JM PVC 50, 60, or 80 mil	Non-combustible	A	1:12	ENRGY 3® (Optional)	Invinsa
JM PVC 50, 60, or 80 mil		B	2:12		
JM TPO 45, 60, or 80 mil		A	½:12		
JM EPDM 45 FR, 60 FR or 90 FR		A	1:12		

### JM Single Ply Systems - Mechanically Fastened

Membrane	Deck	Class	Slope	Insulation	Cover Board
JM PVC 50, 60, or 80 mil	Non-combustible	A	2:12	ENRGY 3® (Optional)	Invinsa
JM PVC 50, 60, or 80 mil		B	2½:12		
JM TPO 45, 60, or 80 mil		A	1:12		

### JM Bituminous Systems - Self Adhered

Membrane	Deck	Class	Slope	Insulation	Cover Board
JM CleanBond® ♦	Non-combustible	A	½:12	ENRGY 3® (Optional)	Invinsa
JM CleanBond® •	Combustible	A	½:12		

- ♦ Minimum 2 ply system
- Minimum 3 ply system