

Standard EPDM Accessories

| Use | SKU | Product | Description | Size | Colors | Packaging |
|--|--|------------------------------------|--|---|--|--|
| | 70000080 70000081 | JM EPDM Tape Primer/Wash | Solvent-based primer designed to prepare EPDM surfaces for peel and stick tape products or lap cement. | 2.5 gal (9.46 l) pails or (6) 1 gal (3.8 l) cans/box | Black | 2.5 gal (9.46 l) pails or (6) 1 gal (3.8 l) cans/box |
| | 70000636 | JM EPDM Tape Primer/Wash (Low VOC) | Organic solvent mixture designed to thoroughly clean the release agent and dirt from JM EPDM membrane prior to applying primers or splice adhesive. | 1 gal (3.78 l) cans | Black | (6) 1 gal (3.8 l) cans/box |
| | 70000082 | Splice Cleaner | Organic solvent mixture designed to thoroughly clean the release agent and dirt from JM EPDM membrane prior to applying primers or splice adhesive. | 5 gal (18.92 l) can | Clear/Colorless | (1) 5 gal (18.92 l) can |
| Membrane and Flashing Accessories | 70000086 70000087 70000088 70000089 70000090 | Flashing | 60 mil uncured EPDM sheet flashing for use in flashing and joints at corners and projections. | 6" x 100' (15.24 cm x 30.48 m) 9" x 100' (22.86 cm x 30.48 m) 12" x 100' (30.48 cm x 30.48 m) 18" x 100' (45.72 cm x 30.48 m) 24" x 100' (60.96 cm x 30.48 m) | Black | 2 rolls/box 1 rolls/box 1 roll/box 1 roll/box 1 roll/box |
| | 70000101 | RTS | Polyester scrim reinforced, cured EPDM strip for securing membranes at perimeters and penetrations. | 6" x 100' (15.24 cm x 30.48 m) | Black | 2 rolls/box |
| | 70000100 | Protective Stone Mat | Nominal 6.0 oz/yd ² (140 g/m ²) UV-resistant polypropylene, needle-punched fabric used as a slipsheet between membrane and ballast or pavers. | 15' x 300' (4.57 m x 91.44 m) | Black | 1 roll |
| Peel & Stick Membrane and Flashing Accessories | 70000097 70000098 | Seam Tape | Self-adhering, cured EPDM/butyl rubber splice tape for splicing EPDM sheets. | 3' x 100' (91.44 cm x 30.48 m) 6' x 100' (1.83 m x 30.48 m) | Black | 4 rolls/box 2 rolls/box |
| | 70000546 70000545 | Flashing | Uncured EPDM sheet with a factory laminated, self-adhering EPDM/butyl tape for corners and projections. | 6" x 100' (15.24 cm x 30.48 m) 12" x 50' (30.48 cm x 18.29 m) | Black | 6" - 2 rolls/box 12" - 1 roll/box |
| | 70000094 70000095 70000096 | Sealing Strip | Cured EPDM strip with factory laminated, self-adhering seam tape to strip in flashing details or field seams. | 6" x 100' (15.24 cm x 30.48 m) 9" x 100' (22.86 cm x 30.48 m) 12" x 100' (30.48 cm x 30.48 m) | Black | 2 rolls/box 1 roll/box 1 roll/box |
| | 70000102 | RTS with Tape | Polyester scrim reinforced, cured EPDM strip with a factory-laminated, 3" (80 mm) self-adhering seam tape for securing membranes at perimeters and penetrations. | 6" x 100' (15.24 cm x 30.48 m) | Black | 2 rolls/box |
| | 70000099 | T-Joint Patches | Uncured EPDM sheets with a factory laminated, self-adhering EPDM/Butyl tape for use where seam laps intersect perimeter or header sheets. | 6" (15.24 cm) round | Black | 100 patches/box |
| | 70000085 | Inside/Outside Corners | Uncured flashing with a pre-applied peel and stick tape. | 7" x 9" (1.75 cm x 2.25 cm) | Black | 20 corners/box |
| | 70000084 | Pipe Boots | Cone-shaped, stepped pipe boot with a pressure sensitive seam tape around the bottom. For use in flashing round roof penetrations. | 1" - 6" (25 mm - 15.24 cm) | Black | 10 boots/box |
| | 70000093 | Pourable Sealer Pockets | One-piece, prefabricated units with a factory-laminated, pressure sensitive seam tape for use in sealing uneven penetrations. | 6" (15.24 cm) diameter 2 1/2" (6.4 cm) base flange | Black | 12 pockets/box |
| | 70000104 | Walkpads | Heavy duty, solid rubber pads with a 3" (7.62 cm) pre-applied tape designed to protect roofs from damaging foot traffic. | 3/8" h x 30" w x 30" l | Black | 50 pads/pallet |
| | Adhesives and Sealants | 70000076 | Bonding Cement (Solvent Based) | One-part, neoprene rubber-based, solvent-based contact adhesive for adhering membrane to porous surfaces such as roof insulation wood or concrete. | 5 gal (18.92 l) can | Yellow |
| 70000077 | | Bonding Cement (Water Based) | One-part, single surface applied polymeric water-based bonding adhesive. | 5 gal (18.92 l) can | Liquid - Milky White Dried Film - Nearly Transparent | (45) 5 gal (18.92 l) cans/pallet |
| 70000626 | | Bonding Cement (Low VOC) | Synthetic rubber adhesive for adhering membrane to porous substrates such as a roof insulation, wood or concrete. | 5 gal (18.92 l) can | Amber | (45) 5 gal (18.92 l) cans/pallet |
| 70000078 | | Lap Cement | One-part, butyl rubber-based, solvent-based contact cement designed to splice adjoining sections of cured or uncured EPDM membrane. | 5 gal (18.92 l) can | Black | 5 gal (18.92 l) can |
| 70000073 70000072 | | Lap Caulk | Heavy bodied, aliphatic, solvent-based, rubber sealant used to seal exposed edges of membrane cement splices. May be used as a temporary nighttime seal. | 10.3 oz (305 ml) cartridges 5 gal (18.9 l) cans | Black | 10 cartridges/box |
| 70000071 | | Pourable Sealer | Two-part, polyurethane sealant used to seal around hard-to-flash membrane penetrations such as pipe clusters and other closely situated penetrations. | Part A: 1 gal (3.8 l) can Part B: 1 pint (0.5 l) container | Black | 3 kits/box |
| 70000289 | | JM Single Ply Sealing Mastic | One-part, gun grade butyl sealant used to seal JM Single Ply membranes and flashings to roof drains and other compression seal applications. | 11 oz (325.31 ml) tube | Grey | 10 tubes/box |



JM EPDM Selector Guide (continued)

| Use | SKU | Product | Description | Size | Colors | Packaging |
|----------------------------|--|-------------------------|---|---|----------------|---|
| Specialty Roofing Products | 90000174 90000176 90000177 90000178 90000179 90000180 90000181 | Expand-O-Flash EJ/WC | Curb-to-curb or curb-to-wall expansion joint consisting of foam-supported bellows with attachment nailing flanges. Designed to manage multidirectional movement of the roofing systems. | 4" - 12" (10.16 cm - 30.48 cm) Bellows 10', 50' or 100' (3.05 m, 15.24 m or 30.48 m) rolls | White or Black | 10', 50' or 100' (3.05 m, 15.24 m or 30.48 m) rolls |
| | 90000643 | Metal/Membrane Flashing | Nominal 6" (15.24 cm) strip of JM EPDM membrane secured (using a patented method) to a nominal 4" (10.16 cm) wide nailing flange, Type 100G-6, galvanized steel. | Membrane - 6" (15.24 cm) w Nailing Flange - 2" - 4" (5.08 cm - 10.16 cm) | Black | 100 lin ft (30.48 lin m)/carton |