

Standard EPDM Accessories

Use	Product	Description	Size	Colors	Packaging
	JM EPDM Tape Primer/Wash	Solvent-based primer designed to prepare EPDM surfaces for peel and stick tape products or lap cement.	2.5 gal (9.46 l) pails or (6) 1 gal (3.8 l) cans/box	Black	2.5 gal (9.46 l) pails or (6) 1 gal (3.8 l) cans/box
	JM EPDM Tape Primer/Wash (Low VOC)	Organic solvent mixture designed to thoroughly clean the release agent and dirt from JM EPDM membrane prior to applying primers or splice adhesive.	1 gal (3.78 l) cans	Black	(6) 1 gal (3.8 l) cans/box
	Splice Cleaner	Organic solvent mixture designed to thoroughly clean the release agent and dirt from JM EPDM membrane prior to applying primers or splice adhesive.	5 gal (18.92 l) can	Clear/Colorless	(1) 5 gal (18.92 l) can
Membrane and Flashing Accessories	Flashing	60 mil uncured EPDM sheet flashing for use in flashing and joints at corners and projections.	6' x 100' (15.24 cm x 30.48 m) 9' x 100' (22.86 cm x 30.48 m) 12' x 100' (30.48 cm x 30.48 m) 18' x 100' (45.72 cm x 30.48 m) 24' x 100' (60.96 cm x 30.48 m)	Black	3 rolls/box 2 rolls/box 1 roll/box 1 roll/box 1 roll/box
	RTS	Polyester scrim reinforced, cured EPDM strip for securing membranes at perimeters and penetrations.	6' x 100' (15.24 cm x 30.48 m)	Black	3 rolls/box
	Protective Stone Mat	Nominal 6.0 oz/yd ² (140 g/m ²) UV-resistant polypropylene, needle-punched fabric used as a slipsheet between membrane and ballast or pavers.	15' x 300' (4.57 m x 91.44 m)	Black	1 roll
Peel & Stick Membrane and Flashing Accessories	Seam Tapes	Self-adhering, cured EPDM/butyl rubber splice tape for splicing EPDM sheets.	3' x 100' (91.44 cm x 30.48 m) 6' x 100' (1.83 m x 30.48 m)	Black	4 rolls/box 2 rolls/box
	Flashings	Uncured EPDM sheet with a factory laminated, self-adhering EPDM/butyl tape for corners and projections.	6' x 100' (15.24 cm x 30.48 m) 12' x 50' (30.48 cm x 18.29 m)	Black	6" - 2 rolls/box 12" - 1 roll/box
	Sealing Strip	Cured EPDM strip with factory laminated, self-adhering seam tape to strip in flashing details or field seams.	6' x 100' (15.24 cm x 30.48 m) 9' x 100' (22.86 cm x 30.48 m) 12' x 100' (30.48 cm x 30.48 m)	Black	2 rolls/box 1 roll/box 1 roll/box
	RTS with Tape	Polyester scrim reinforced, cured EPDM strip with a factory-laminated, 3" (80 mm) self-adhering seam tape for securing membranes at perimeters and penetrations.	6' x 100' (15.24 cm x 30.48 m)	Black	2 rolls/box
	T-Joint Patches	Uncured EPDM sheets with a factory laminated, self-adhering EPDM/Butyl tape for use where seam laps intersect perimeter or header sheets.	6' (15.24 cm) round	Black	20 patches/box
	Inside/Outside Corners	Uncured flashing with a pre-applied peel and stick tape.	7" x 9" (1.75 cm x 2.25 cm)	Black	20 corners/box
	Pipe Boots	Cone-shaped, stepped pipe boot with a pressure sensitive seam tape around the bottom. For use in flashing round roof penetrations.	1" - 6" (25 mm - 15.24 cm)	Black	10 boots/box
	Pourable Sealer Pocket	One-piece, prefabricated units with a factory-laminated, pressure sensitive seam tape for use in sealing uneven penetrations.	6" (15.24 cm) diameter 2 1/2" (6.4 cm) base flange	Black	12 pockets/box
	Walkpads	Heavy duty, solid rubber pads with a 3" (7.62 cm) pre-applied tape designed to protect roofs from damaging foot traffic.	3/8" h x 30" w x 30" l	Black	50 pads/pallet
Adhesives and Sealants	Bonding Cement (Solvent Based)	One-part, neoprene rubber-based, solvent-based contact adhesive for adhering membrane to porous surfaces such as roof insulation wood or concrete.	5 gal (18.92 l) can	Yellow	(45) 5 gal (18.92 l) cans/pallet
	Bonding Cement (Water Based)	One-part, single surface applied polymeric water-based bonding adhesive.	5 gal (18.92 l) can	Liquid - Milky White Dried Film - Nearly Transparent	(45) 5 gal (18.92 l) cans/pallet
	Bonding Cement (Low VOC)	Synthetic rubber adhesive for adhering membrane to porous substrates such as a roof insulation, wood or concrete.	5 gal (18.92 l) can	Amber	(45) 5 gal (18.92 l) cans/pallet
	Lap Cement	One-part, butyl rubber-based, solvent-based contact cement designed to splice adjoining sections of cured or uncured EPDM membrane.	5 gal (18.92 l) can	Black	5 gal (18.92 l) can
	Lap Caulk	Heavy bodied, aliphatic, solvent-based, rubber sealant used to seal exposed edges of membrane cement splices. May be used as a temporary nighttime seal.	10.3 oz (305 ml) cartridges 5 gal (18.9 l) cans	Black	10 cartridges/box
	Pourable Sealer	Two-part, polyurethane sealant used to seal around hard-to-flash membrane penetrations such as pipe clusters and other closely situated penetrations.	Part A: 1 gal (3.8 l) can Part B: 1 pint (0.5 l) container	Black	3 kits/box
	JM Single Ply Sealing Mastic	One-part, gun grade butyl sealant used to seal JM Single Ply membranes and flashings to roof drains and other compression seal applications.	11 oz (325.31 ml) tube	Grey	10 tubes/box
Specialty Roofing Products	Expand-O-Flash EJ/WC	Curb-to-curb or curb-to-wall expansion joint consisting of foam-supported bellows with attachment nailing flanges. Designed to manage multidirectional movement of the roofing systems.	4" - 12" (10.16 cm - 30.48 cm) Bellows 10', 50' or 100' (3.05 m, 15.24 m or 30.48 m) rolls	White or Black	10', 50' or 100' (3.05 m, 15.24 m or 30.48 m) rolls
	Metal/Membrane Flashing	Nominal 6" (15.24 cm) strip of JM EPDM membrane secured (using a patented method) to a nominal 4" (10.16 cm) wide nailing flange, Type 100G-6, galvanized steel.	Membrane - 6" (15.24 cm) w Nailing Flange - 2" - 4" (5.08 cm - 10.16 cm)	Black	100 lin ft (30.48 lin m)/carton