

JM TPO Membrane Selector Guide

Description	Product	ASTM	Thickness	Color			Sizes Width x Length	Area per Roll	Weight	Specifications		Guarantees		
				White	Grey	Tan				Mechanically Fastened	Fully Adhered			
Thermoplastic, polyester reinforced membrane manufactured using an ultraviolet-resistant TPO (thermoplastic polyolefin) formulation.	JM TPO	D 6878	45 mil	X	*	*	5' x 100' (1.52 m x 30.48 m)	500 ft ² (46.45 m ²)	130 lb (58.97 kg)	ST4RM-S/ ST4RM-S/I ST4RM-W	ST4RA-S ST4RA-S/I ST4RA-C ST4RA-C/I	5 or 10 yr NDL		
				X	*	*	8' x 100' (2.44 m x 30.48 m)	800 ft ² (74.32 m ²)	208 lb (94.35 kg)					
				X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	258 lb (117.03 kg)					
			60 mil	X	X	X	5' x 100' (1.52 m x 30.48 m)	500 ft ² (46.45 m ²)	162 lb (73.48 kg)	ST6RM-S ST6RM-S/I ST6RM-W	ST6RA-S ST6RA-S/I ST6RA-C ST6RA-C/I	5, 10, 15, or 20 yr NDL		
				X	*	*	8' x 100' (2.44 m x 30.48 m)	800 ft ² (74.32 m ²)	256 lb (116.19 kg)					
				X	X	X	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	322 lb (146.06 kg)					
			80 mil	X	*	*	5' x 75' (1.52 m x 22.86 m)	375 ft ² (34.84 m ²)	216 lb (97.98 kg)					5, 10, 15, or 20 yr NDL
				X	*	*	8' x 75' (2.44 m x 22.86 m)	600 ft ² (55.74 m ²)	347 lb (157.40 kg)					
				X	*	*	10' x 75' (3.04 m x 22.86 m)	750 ft ² (69.68 m ²)	434 lb (196.86 kg)					
Thermoplastic polyolefin (TPO) membrane with a reinforced polyester fabric and integral polyester fleeces backing.	JM TPO FB 100™		45 mil	X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	270 lb (122.47 kg)			5 or 10 yr NDL		
	JM TPO FB 115™		60 mil	X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft ² (92.90 m ²)	325 lb (147.42 kg)			5, 10, 15, or 20 yr NDL		

*Grey and tan are special order.