

# JM TPO Membrane (JM Brand) Selector Guide

Description	Product	ASTM	Thickness	Color			Sizes	Area per Roll	Weight	Specifications		Guarantees
				White	Grey	Tan	Width x Length			Mechanically Fastened	Fully Adhered	Mechanically Fastened and Fully Adhered
Thermoplastic, polyester reinforced membrane manufactured using an ultraviolet-resistant TPO (thermoplastic polyolefin) formulation.	JM TPO	D 6878	45 mil	X	*	*	5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	130 lb (58.97 kg)	ST4RM-S ST4RM-S/I ST4RM-W	ST4RA-S ST4RA-S/I ST4RA-C ST4RA-C/I	5 or 10 yr NDL
				X	n/a	n/a	8' x 100' (2.44 m x 30.48 m)	800 ft <sup>2</sup> (74.32 m <sup>2</sup> )	208 lb (94.35 kg)			
				X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	258 lb (117.03 kg)			
			60 mil	X	*	*	5' x 100' (1.52 m x 30.48 m)	500 ft <sup>2</sup> (46.45 m <sup>2</sup> )	162 lb (73.48 kg)	ST6RM-S ST6RM-S/I ST6RM-W	ST6RA-S ST6RA-S/I ST6RA-C ST6RA-C/I	5, 10, 15, or 20 yr NDL
				X	n/a	n/a	8' x 100' (2.44 m x 30.48 m)	800 ft <sup>2</sup> (74.32 m <sup>2</sup> )	256 lb (116.19 kg)			
				X	*	*	10' x 100' (3.04 m x 30.48 m)	1,000 ft <sup>2</sup> (92.90 m <sup>2</sup> )	322 lb (146.06 kg)			
			80 mil	X	n/a	n/a	5' x 75' (1.52 m x 22.86 m)	375 ft <sup>2</sup> (34.84 m <sup>2</sup> )	216 lb (97.98 kg)			5, 10, 15, or 20 yr NDL
				X	n/a	n/a	8' x 75' (2.44 m x 22.86 m)	600 ft <sup>2</sup> (55.74 m <sup>2</sup> )	347 lb (157.40 kg)			
				X	n/a	n/a	10' x 75' (3.04 m x 22.86 m)	750 ft <sup>2</sup> (69.68 m <sup>2</sup> )	434 lb (196.86 kg)			

\*Grey and tan are special order.