



JM EPDM Peel & Stick Inside/Outside Corners

Description

JM EPDM Peel & Stick Inside/Outside Corners consist of 60 mil thick (1.52 mm) uncured flashing with a pre-applied peel and stick tape.

Use

Use universally for either an inside or outside corner. Quick and easy to install.

Color

Black

Specifications

Thickness

Membrane Thickness	0.060" (1.52 mm)
Tape Thickness	0.025" (0.64 mm)
Total Thickness	0.085" (2.16 mm)

Size..... 7" x 9" (17.78 cm x 22.86 cm)

Packaging

20 per box

Weight

5 lb (2.26 kg) per box

Shelf Life

Six months from manufacture date when stored properly (see storage section). Storage temperatures exceeding 80°F (27°C) may affect shelf life.

Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F and 80°F (16°C and 27°C).

Application

Refer to JM EPDM Applicator Guides or Detail Drawings for instructions.

Precautions

Do not install in direct contact with asphalt or coal tar pitch. A heat gun is required for forming outside corners in colder temperatures.

Refer to the Material Safety Data Sheet prior to using JM EPDM Peel & Stick Inside/Outside Corners. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.