



JM EPDM Peel & Stick T-Joint Patches

Description

JM EPDM Peel & Stick T-Joint Patches are 6" (15.24 cm) round, uncured EPDM (ethylene propylene diene monomer) sheets with a factory laminated, self-adhering EPDM/butyl tape. This product is formulated to 1) provide high initial strength in both peel and shear at typical rooftop temperatures and 2) improve the speed and quality of field seaming on JM EPDM roofing systems.

Use

To seal seam laps where perimeter or header sheets intersect. This product is often used as an alternative to solvent-based contact adhesives.

Color

Black

Specifications

Thickness

Membrane Thickness	0.045" (1.14 mm)
Tape Thickness	0.025" (0.64 mm)
Total Thickness	0.070" (1.78 mm)
Size	6" (15.24 cm) round

Packaging

20 patches per box

Weight

2 lb (0.9 kg) per box

Shelf Life

Six months from manufacture date when stored properly (see storage section). Storage temperatures exceeding 80°F (27°C) may affect shelf life.

Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F and 80°F (16°C and 27°C).

Application

Refer to JM EPDM Applicator Guides or Detail Drawings for instructions.

Precautions

Do not install in direct contact with asphalt or coal tar pitch.

Refer to the Material Safety Data Sheet prior to using JM EPDM Peel & Stick T-Joint Patches. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.