



JM EPDM/PVC Pourable Sealer

Description

JM EPDM/PVC Pourable Sealer is a two-part polyurethane sealant. It is used as a penetration pocket filler.

Colors

Part A: Black
Part B: Amber

Container Size

Part A: 1 gal (3.8 l) can
Part B: 1 pint (0.5 l) container

Kits Per Box

Three

Weight Per Box

34 lb (15.4 kg)

Shelf Life

Twelve months when stored between 40°F and 80°F (4°C and 27°C)

Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F and 75°F (16°C and 24°C). Avoid moisture contamination. Keep container closed when not in use.

Installation

Clean penetration pockets to be sealed, ensuring surfaces are free of moisture, dirt and any other contaminants. Pour contents of the Part B can into the Part A 1 gal (3.8 l) can. Stir thoroughly by hand or mechanical means until marble effect disappears. Apply the JM EPDM/PVC Pourable Sealer into the penetration pocket, making sure there is complete contact with all surfaces. Shake slightly to shed water. **DO NOT THIN OR USE PARTIAL QUANTITIES.**

IMPORTANT: Workable pot life after mixing is approximately 30 minutes at 72°F (22°C). The material begins to cure firmly 2 hours after mixing.

Refer to the Applicator Guides or Detail Drawings for instructions.

Precautions

Refer to the Material Safety Data Sheet prior to using JM EPDM/PVC Pourable Sealer. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.