

Description

JM EPDM Reinforced Termination Strip (RTS) With Tape is a black, 6" (15.24 cm) wide, 45 mil (1.14 mm) thick, polyester scrim reinforced, cured EPDM strip with a factory-laminated, 3" (7.62 cm) self-adhering seam tape.

Use

For securing EPDM membranes at perimeters and penetrations.

Color

Black

Physical Properties

JM EPDM Reinforced Termination Strip With Tape

Peel Strength (ASTM D 413 @ 70°F [21°C]). 8 - 10 pli
(1.43 - 1.79 kg/cm)

Shear Strength (ASTM D 816 @ 70°F [21°C]) 35 - 45 psi
(241 - 310 kPa)

Tape Thickness 0.035" (0.89 mm)

Packaging

JM EPDM Reinforced Termination Strip With Tape

(2) 100' (30.48 m) rolls/box; 200 lin ft/box (60.96 lin m/box)

38 lb (17 kg) per box

Roll Size:

6" x 100' (15.24 cm x 30.48 m)



Shelf Life

One year from manufacture date when stored properly (see storage section).

Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F and 80°F (16°C and 27°C).

Application

Refer to JM EPDM Applicator Guides or Detail Drawings for instructions.

Precautions

Do not install in direct contact with asphalt or coal tar pitch.

Refer to the Material Safety Data Sheet prior to using JM EPDM Reinforced Termination Strips. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.