

## Description

JM EPDM Splice Cleaner is an organic solvent mixture designed as a cleaning agent.

## Colors

Clear and colorless

## Use

Use to thoroughly clean the release agent and dirt from JM EPDM (ethylene propylene diene monomer) membranes prior to applying primers or splice adhesives.

## Physical Properties

Benzene Content .....	<0.01% max.
Weight .....	6.20 lb/gal (0.74 kg/l)
Flash Point (TCC) .....	50°F (-10°C)
Viscosity .....	<50 cps

## Coverage

Application rate will vary depending on the amount of release agent and contaminants, such as dirt and debris.

## Packaging

5 gal (18.9 l) pails



## Shelf Life

One year from manufacture date when stored properly (see storage section) in unopened containers. Storage temperatures exceeding 90°F (32°C) may affect shelf life.

## Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F and 80°F (16°C and 27°C) in the original, unopened container. Always rotate stock.

## Application

Refer to JM EPDM Applicator Guides or Detail Drawings for instructions.

## Precautions

**Do not install in direct contact with asphalt or coal tar pitch.**

**Refer to the Material Safety Data Sheet prior to using JM EPDM Splice Cleaner. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**