



Single Ply Roofing Systems (EPDM) JM EPDM Tape Primer/Wash

Description

JM EPDM Tape Primer/Wash is a solvent-based primer designed to aid in the lap seaming process.

Use

To prime the EPDM (ethylene propylene diene monomer) surface for EPDM tape products.

Color

Black

Coverage

250 - 400 ft²/gal (6.14 - 9.82 m²/l)

Packaging

2.5 gal (9.5 l) pail – 17.5 lb (7.94 kg)/pail
(6) 1 gal (3.8 l) cans/box – 42 lb (19 kg)/box

Shelf Life

Nine months from manufacture date when stored properly (see storage section) in unopened containers.

Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F and 80°F (16°C and 27°C) in the original, unopened container. Always rotate stock.

Application

Refer to JM EPDM Applicator Guides or Detail Drawings for instructions.

Precautions

Do not install in direct contact with asphalt or coal tar pitch.

Keep can or pail tightly closed when not in use and protect from moisture contamination. Once exposed to moisture in the air, JM EPDM Tape Primer/Wash begins to cure and may gel within 24 hours.

Refer to the Material Safety Data Sheet prior to using JM EPDM Tape Primer/Wash. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.