



Single Ply Roofing Systems (PVC)

JM Polyester Mat Protection Slipsheet

Description

JM Polyester Mat Protection Material 9 oz/yd² (0.31 kg/m²) is a needle-punched polyester fabric. It is intended for use as a cushioning layer on concrete decks prior to installing a ballasted system and as a separation layer between extruded polystyrene insulation and roofing membrane in protected membrane (inverted) roof assemblies. It is also used as a protective layer between pavers and JM single ply membranes.

Color

White

Material

9.0 oz/yd² (0.31 kg/m²) polyester

Roll Size

12' wide x 100' long (3.7 m x 30.48 m)

Roll Coverage

1,200 ft² (111.48 m²) (gross)

Weight Per Roll

84 lb (38.1 kg)

Storage

JM Polyester Mat Protection Slipsheet should be stored in a cool, dry location.

Installation

JM Polyester Mat Protection Slipsheet is typically installed between the overlying extruded polystyrene insulation and JM PVC roofing membrane. It is installed loosely laid with 4" (10.16 cm) overlap. Taping of joints is **not** required.

Precautions

Care must be taken when installing the JM Polyester Mat Protection Slipsheet to avoid tearing and puncturing.

Refer to the Material Safety Data Sheet prior to using JM Polyester Mat Protection Slipsheet. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.