



JM PVC Detail Strip

Description

JM PVC Detail Strips are flexible strips of polyester-reinforced, thermoplastic membrane manufactured using an ultraviolet-resistant polyvinyl chloride and an Elvaloy® KEE (ketone ethylene ester) formulation. JM PVC Detail Strips are used primarily to waterproof joints of JM PVC-Coated Metal.

Packaging

Roll

Nominal Thickness

0.060" (1.52 mm)

Size

6" x 150' (15.2 cm x 45.7 m)

8" x 150' (20.32 cm x 45.72 m)

Colors

6" x 150' (15.2 cm x 45.7 m)	Black/White
8" x 150' (20.32 cm x 45.72 m)	White/Grey and Sandstone/White

Coverage

6" x 150' (15.2 cm x 45.7 m)	100 ft ² (9.29 m ²)
8" x 150' (20.32 cm x 45.72 m)	75 ft ² (6.97 m ²)

Weight

6" x 150' (15.2 cm x 45.7 m)	30 lb (13.6 kg)
8" x 150' (20.32 cm x 45.72 m)	40 lb (18.1 kg)

Storage

JM PVC Detail Strip should be kept dry and clean prior to installation.

Installation

Refer to JM PVC Applicator Guides or Detail Drawings for instructions.

Precautions

Do not install JM PVC Detail Strip in direct contact with asphalt or coal tar pitch.

Refer to the Material Safety Data Sheet prior to using JM PVC Detail Strip. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.