

## Lightweight Concrete (LWC) Pre-Assembled Base Sheet Fasteners

### Description

LWC Pre-Assembled Base Sheet Fasteners are twin-legged, expanding base sheet fasteners with 2.7" (6.9 cm) Galvalume®\*-coated steel plates.

### Use

Use to attach venting and other approved base and ply sheets to lightweight insulating concrete roof decks. The minimum deck thickness is 2" (5.08 cm). Conduct pullout tests to determine actual retention strength. Minimum pullout value is 40 pounds force (178 N). The fastener provides positive attachment and resistance to uplift forces.

### Advantages

- Pre-assembled, reducing installation time
- FM Global and Miami-Dade County Product Control Approved
- Corrosion-resistant coating which meets FM Global® Approval Standard #4470
- FM Global 1-60 and 1-90 approved in specific constructions
- Requires no special driving tools
- Sturdy, steel construction



### Sizes and Packaging

1.2" (3.05 cm) length	1,000/box
1.7" (4.32 cm) length	500/box

### Precautions

**Refer to the Material Safety Data Sheet prior to using Lightweight Concrete Pre-Assembled Base Sheet Fasteners. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**

\*Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.