



JM PVC Roofing Systems Guarantee/Spec Matrix

System	Term	System Type	Membrane	Spec	Insulation Substrate	Notes
BEST	20 year NDL	Mechanically Fastened	JM PVC 80 or JM PVC 60	SP8RM SP6RM	None: 60 mil or 80 mil JM PVC Fleece-Backed Membrane (LWC only) OR <u>One Layer:</u> WF, I, E, TE OR <u>Two Layers:</u> (Choose 1, each layer) Top: WF, I, E, TE, DD Bottom: E, TE	1. New construction or complete tear-off only. Re-covers allowed only with a full, non-destructive moisture survey with conforming core cuts. All wet materials must be removed and replaced with new materials or removal of existing roof cover. 2. Refer to specifications for specific system requirements. 3. Insulation must be JM (except DD).
			JM PVC 80 Fleece Backed or JM PVC 60 Fleece Backed	SP8PM SP6PM		
		Fully Adhered	JM PVC 80 or JM PVC 60	SP8RA SP6RA		
			JM PVC 80 Fleece Backed or JM PVC 60 Fleece Backed	SP8PA SP6PA		
BETTER	15 year NDL	Mechanically Fastened	JM PVC 60 or JM PVC 50	SP6RM SP5RM	None: 60 mil or 80 mil JM PVC Fleece-Backed Membrane (LWC only) OR <u>One Layer:</u> WF, I, E, TE, DD* OR <u>Two Layers:</u> (Choose 1, each layer) Top: WF, I, E, TE, DD Bottom: E, TE	1. Retrofit installations require that blisters, buckles and ridges shall be cut and patched to provide a reasonably level substrate surface. 2. Refer to specifications for specific system requirements. 3. Insulation must be JM (except DD).
			JM PVC 60 Fleece Backed or JM PVC 50 Fleece Backed	SP6PM SP5PM		
		Fully Adhered	JM PVC 60 or JM PVC 50	SP6RA SP5RA		
			JM PVC 60 Fleece Backed or JM PVC 50 Fleece Backed	SP6PA SP5PA		
GOOD	5 or 10 year NDL	Mechanically Fastened	JM PVC 50 or JM PVC 50 Fleece Backed	SP5RM SP5PM	None: 60 mil or 80 mil JM PVC Fleece-Backed Membrane (LWC only) OR <u>One Layer:</u> WF, I, E, TE, DD OR <u>Two Layers:</u> (Choose 1, each layer) Top: WF, I, E, TE, DD Bottom: E, TE	
			JM PVC 50 or JM PVC 50 Fleece Backed	SP5RA SP5PA		
		Fully Adhered	JM PVC 50 or JM PVC 50 Fleece Backed	SP5RA SP5PA		
			JM PVC 50 or JM PVC 50 Fleece Backed	SP5RA SP5PA		

Insulation and Cover Boards

WF = Wood Fiber

I = Invinsa Roof Board

DD = DensDeck®

E = ENRGY 3/ISO 3

TE = Tapered ENRGY 3/Tapered ISO 3

Deck

LWC = Lightweight
Insulating Concrete

DensDeck is a registered trademark of Georgia-Pacific, LLC.

* Summit and Pinnacle Peak Advantage Contractors only.
Refer to the JM Single Ply Guarantee Charges and Requirements pages for
more information on 25 and 30 year options. Contact Technical Services, your
local JM sales representative or the Web for more information.