

Description

Polymer Auger Fasteners are glass-reinforced nylon fasteners with an internal $\frac{1}{4}$ " (6 mm) square drive. Polymer Auger Fasteners have a 1" (2.5 cm) diameter head.

Polymer Auger Fasteners are available with Galvalume®*-coated, metal stress plates:

- 2" (5.1 cm) round, barbed membrane plate, designed for grip
- 3" (7.6 cm) square insulation plate, designed to lock into the Polymer Auger fastener head.

The fasteners and plates do not come pre-assembled.

Use

Use for fastening roof insulation to either cementitious wood fiber or gypsum roof decks. The fastener and plate system provides positive attachment and resistance to uplift forces.

A pullout test to determine the integrity of the deck is required for all Polymer Auger installations.

Advantages

- Increased pullout and backout resistance.
- Minimized fastener breakage.
- Fast, easy installation.
- Polymer Auger Fasteners are FM Global® and Miami-Dade County Product Control Approved.
- Reduction in thermal bridging.



Sizes and Packaging

Fastener:	2½" to 7½" (6.4 cm to 19.1 cm)	500/box
Plates:	2" or 3" (5.1 cm or 7.6 cm)	1,000/box

Precautions

Refer to the Material Safety Data Sheet prior to using Polymer Auger Fasteners and Plates. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.

*Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.