

Description and Use

Presto Lock Fascia System

The Presto Lock Fascia System is an economical snap-on fascia system designed for use with single ply, built-up and modified bitumen roofing systems. The fascia system consists of a galvanized base piece (Water Dam and Cover Plate) of either galvanized or aluminum. Concealed cover plates complete the system.

Water Dam

10' (3.05 m) sections of 24 gauge (0.61 mm) galvanized are installed over the membrane by attaching to the vertical face and through the skirt onto the roof with standard roofing nails. Sections should be butted together.

Cover Plate

After approved flashing compatible with the roofing membrane is properly installed over the water dam, the cover plate is snapped into place. 10' (3.05 m) sections should be installed with a ½" (12.7 mm) space between each section. Sections should be installed with the joints staggered with those of the Water Dam.

Standard sizes are 7" (17.78 cm) face (covers two, 1½" [3.81 cm] nailers) and 9" (22.86 cm) face (covers three nailers). These lengths are available in combinations of the following gauge and finish:

Aluminum

- **Gauges:** 0.040" (1.02 mm)
0.050" (1.27 mm)
0.063" (1.6 mm)
- **Finish:** Mill, Kynar 500

Galvanized

- **Gauges:** 22 gauge (0.76 mm)
24 gauge (0.61 mm)
- **Finish:** Kynar 500

Cover Plates are made of 0.050" (1.27 mm) aluminum mill finish, clear anodized, Kynar®* 500 or 24 gauge (0.71 mm) galvanized Kynar 500 finish. Standard sizes are 7" (17.78 cm) face (covers two 1½" [3.81 cm] thick nailers) and 9" (22.86 cm) face (covers three nailers). Concealed Cover Plates of the same color and material as the Cover Plate are installed behind each joint of the Cover Plate. These simply snap into place. The other 28 standard Kynar colors are also available.



Extender Plate

For use where additional metal coverage is required. Fits behind the bottom edge of the fascia system and extends downward the required distance from 4" to 14" (10.16 cm to 35.56 cm) in 1" (2.54 cm) increments. This is hooked onto a continuous connector clip at the bottom, and is nailed at the top. Concealed extender plates are placed behind each joint.

Accessories

Inside and outside corners, fascia sumps, and scuppers are available made of the same material and color as the cover plate.

Advantages

- Fast snap-on design
- FM Global® 1-90 (aluminum)
- Special sizes, shapes, metals, and curved fascias are available upon request
- 28 Standard Kynar 500 colors available and special colors available upon request
- Compatible with EPDM and PVC single ply systems and bituminous systems

Approvals/Certifications

FM Global® 1-90 (0.050" [1.27 mm] aluminum)

Refer to the Material Safety Data Sheet and product label prior to using this product.