



## JM EPDM Tape Primer/Wash (Low VOC)

### Description

JM EPDM Tape Primer/Wash (Low VOC) is a solvent-based, fast drying primer with excellent green (tack back) strength. This product has 243 g/L of VOC content meeting VOC regulation requirements.

### Use

JM EPDM Tape Primer/Wash is designed to prime the membrane surface for peel and stick products to aid in the lap seaming process.

### Color

Black

### Coverage

200 - 250 ft<sup>2</sup>/gal (18.58 - 23.23 m<sup>2</sup>/l) as a cleaner/primer  
350 - 400 ft<sup>2</sup>/gal (32.52 - 37.16 m<sup>2</sup>/l) as a brushed on primer

### Packaging

(6) 1 gal (3.8 l) cans/box – 59 lb (27 kg)/box

### Shelf Life

6 months when stored properly (see storage section) in unopened containers.

### Storage

Keep product clean and dry prior to application. Store indoors, out of direct sunlight, at temperatures between 60°F - 80°F (16°C - 27°C) in the original, unopened container. Always rotate stock.

### Application

Stir product before and during use; solids will tend to settle out of product. Apply product at temperatures above 40°F (4°C) and rising to avoid extended drying times and water condensation on the primed area. Do not dilute.

Ensure surface is clean and free of excess talc. Apply with scrubber pad avoiding streaking or puddling. Apply to an area wider than the splice area to insure bonding to primed surfaces. Change scrubber pad when pad becomes dirty. Allow primer to dry until tacky but does not transfer when touched. It is important to ensure the primed surface is sufficiently dry before applying tape. Low VOC primers may take longer than other primers to dry, depending on temperature and humidity.

### Precautions

**Do not install in direct contact with asphalt or coal tar pitch.**

**Keep can or pail tightly closed when not in use and protect from moisture contamination. Once exposed to moisture in the air, JM EPDM Tape Primer/Wash (Low VOC) begins to cure and may gel within 24 hours.**

**Refer to the Material Safety Data Sheet prior to using JM EPDM Tape Primer/Wash (Low VOC). The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**