

Description

JM Single Ply Sealing Mastic is a one-part, gun grade butyl sealant. It is used to seal JM Single Ply Membranes and flashings to roof drains.

Color

Grey

Physical Properties

Weight 25 lb (11.34 kg)/box
 Flash Point 50°F (10°C)
 Butyl Polymer/Solids 82% min.
 Solvents 18% max.

Coverage Rate

15 lin ft (4.57 lin m) per tube

Packaging

(10) 11 oz (325.31 ml) tubes per box

Shelf Life

Nine months when stored between 60°F (16°C) and 80°F (27°C) in unopened container.

Storage

JM Single Ply Sealing Mastic should be stored in a dry area protected from weather and extreme temperatures.

Do not store in direct sunlight.



Installation

Apply JM Single Ply Sealing Mastic to a clean, dry surface only. Apply a minimum 3/8" (9.53 mm) bead to substrate. Mate the surface of the flashing membrane with the mastic and roll to ensure a tight seal. Then apply termination material to secure the waterstop with constant compression. Sealant is a maintenance item and is not covered by the guarantee.

Refer to JM Single Ply Applicator Guides or Detail Drawings for instructions.

Precautions

Use only in well-ventilated areas. Keep away from children and avoid contact with skin. Do not use in applications where the caulk is exposed to direct ultraviolet rays.

Refer to the Material Safety Data Sheet prior to using JM Single Ply Sealing Mastic. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.



Johns Manville
