



JM PVC-Coated Metal

Description

JM PVC-Coated Metal is a laminant of JM PVC membrane and a galvanized steel. It is fabricated by the contractor into metal flashings and edge details. It is used to provide monolithic water-tight protection for both adhered and mechanically fastened roofing assemblies.

Colors

White, Grey, Sandstone, or Black

Material

JM PVC 20 mil (0.51 mm) nonreinforced membrane laminated to 24 gauge (0.6 mm) galvanized steel

Packaging (Sheets/Skid)	30
Sheet Size (ft [m])	4 x 10 (1.22 x 3.05)
Weight (lb [kg])	
Sheet	42 (19)
Skid	1360 (617)

Storage

JM PVC-Coated Metal must be kept dry and clean prior to installation. JM PVC-Coated Metal must be stored flat, not on end, protected from warping, bending or contamination.

Installation

Refer to JM PVC Applicator Guides or Detail Drawings for instructions.

Precautions

Do not install JM PVC-Coated Metal in a manner where the membrane side would be in direct contact with asphalt, coal tar pitch, or any petroleum-based product.

Refer to the Material Safety Data Sheet prior to using JM PVC-Coated Metal. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.