

### Description

JM PVC Pipe Boots are smooth, cone-shaped boots manufactured with a flexible, nonreinforced thermoplastic membrane using an ultraviolet-resistant polyvinyl chloride and an Elvaloy® KEE (ketone ethylene ester) formulation.

Each boot has a cutting guide for easy reference and diameter measurements. JM PVC Pipe Boots accommodate pipe sizes from 1" to 6" (2.5 cm to 15.2 cm) in diameter. Standard size pipe clamps covering the largest possible range (6" diameter) are included for each pipe boot. Dimensions less than 1.5" diameter may require alternative clamps. Standard pipe boots are heat welded to JM PVC Membrane.

### Use

Use in traditional or split-pipe flashing applications to securely seal the penetration. Pipe boots eliminate the need for field fabrication.

### Sizes

1" - 6" (2.5 cm - 15.2 cm) Standard

### Colors

White, Grey, Sandstone

### Weight

1.2 lb (0.54 kg) ea.  
12 lb (5.44 kg)/box

### Packaging

10 boots and clamps/box



### Storage

Keep JM PVC Pipe Boots clean and dry prior to installation. Protect from extreme temperatures and physical damage. Store at temperatures between 60°F and 80°F (16°C and 27°C).

### Installation

Apply JM PVC Pipe Boots in accordance with JM PVC Application Guides or detail drawings.

### Precautions

**Refer to the Material Safety Data Sheet prior to using JM PVC Pipe Boots. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**