



JM DN Flameguard Slipsheet

Description

The JM DN Flameguard Slipsheet is a laminated aluminum foil/kraft paper slipsheet with a proprietary flame-extinguishing adhesive and a fiber glass scrim reinforcement. It is intended for use with mechanically attached systems as a fire-retardant slipsheet in certain UL and/or FM assemblies and in re-cover assemblies over coal tar pitch.

Color

Foil/brown

Material

.000351" (0.009 mm) aluminum foil fiber glass scrim
30 lb (13.6 kg) kraft paper

Packaging

Roll size: 71" wide x 700' long (1.8 0m x 213.36 m) long

Roll Coverage

4,142 ft² (384.80 m²)

Weight Per Roll

100 lb (45.4 kg)

Storage

JM DN Flameguard Slipsheet should be stored in a cool, dry location.

Installation

The JM DN Flameguard Slipsheet is typically installed between the JM PVC roofing membrane and insulation substrate. It is installed foil side up, loosely laid with 4" (10.16 cm) lap joints. Taping of joints is **not** required.

Refer to JM PVC Applicator Guides or Detail Drawings for instructions.

Precautions

Refer to the Material Safety Data Sheet prior to using JM DN Flameguard Slipsheet. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.