

## Description

JM TPO Membrane Primer is a synthetic polymer-based primer designed for preparation of JM TPO Membrane surfaces to be adhered using JM TPO peel and stick products. It can be used to prime JM TPO peel and stick accessories in a one-step operation.

## Color

Clear to light yellow

## Physical Properties

Weight ..... 6.5 lb/gal (0.8 kg/l)  
 Flash Point ..... 10°F (-12°C)  
 Solids ..... 15% ± 2%  
 Solvents ..... Light Asphaltic Naptha

## Coverage Rate

200 ft<sup>2</sup>/gal (4.9 m<sup>2</sup>/l)

## Packaging

3 gal (11.36 l) can

## Shelf Life

Nine months when stored between 60°F (16°C) and 80°F (27°C) in unopened containers.

## Storage

JM TPO Membrane Primer must be stored in a dry area protected from weather and extreme temperatures until just prior to use.

**Do not store in direct sunlight.**



## Installation

Mix thoroughly. Do not thin. Allow JM TPO Membrane Primer to dry until slightly tacky to a dry finger touch before applying JM TPO peel and stick products.

Clean all surfaces with a clean, natural fiber rag, removing excess contamination before applying JM TPO Membrane Primer. With a scrub pad and a handle, apply JM TPO Membrane Primer to the JM TPO Membrane, where a JM TPO peel and stick product will be applied, using long, continuous back and forth strokes with heavy to moderate pressure until no streaks or puddling occurs.

When cleaning before priming, allow cleaner to dry prior to using primer. Apply primer to the cleaned area with a paint brush at a rate of 350 to 400 ft<sup>2</sup>/gal (8.6 to 9.8 m<sup>2</sup>/l).

Refer to JM TPO Applicator Guides or Detail Drawings for instructions.

## Precautions

**Do not install in direct contact with asphalt.**

**Keep pail tightly closed when not in use, and protect from moisture. Once exposed to moisture in the air, the primer begins to cure and may gel within 24 hours.**

**Use chemically resistant gloves. May cause possible skin irritation. May cause sensitivity in susceptible individuals.**

**Refer to the Material Safety Data Sheet prior to using JM TPO Membrane Primer. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**