

Description

JM TPO Pipe Boots are smooth, cone-shaped boots. Each boot has a cutting guide for easy reference and diameter measurements.

JM TPO Pipe Boots accommodate pipe sizes from 1" to 6" (2.5 cm to 15.2 cm) in diameter. Standard size pipe clamps covering the largest possible range (6" diameter) are included for each pipe boot. Dimensions less than 1.5" diameter may require alternative clamps. Standard pipe boots are heat welded to JM TPO Membrane.

Use

Use in traditional or split-pipe flashing applications to securely seal the penetration. Pipe boots eliminate the need for field fabrication.

Size

1" to 6" (2.54 cm to 15.24 cm)

Colors

White, Grey and Tan

Weight

0.85 lb (0.38 kg) ea.
8.5 lb (3.86 kg)/box

Packaging

10 boots and clamps/box

Storage

Store JM TPO Pipe Boots in a dry area protected from extreme temperatures and physical damage. Store in temperatures between 60°F to 80°F (16°C to 27°C).

Do not store in direct sunlight.



Installation

Install JM TPO products in accordance with current JM TPO Applicator Guides or Detail Drawings.

Precautions

Do not install JM TPO Pipe Boots in direct contact with asphalt. Do not overheat membrane when using hot air tools.

Refer to the Material Safety Data Sheet (MSDS) prior to using JM TPO Pipe Boots. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing.