



Johns Manville

JM TPO Edge Sealant

Description

JM TPO Edge Sealant is a one-part sealing agent used to seal cut edges of JM TPO Membranes where the polyester reinforcement is exposed after cutting. A 1/8" (3.18 mm) bead is applied to the cut edge of the TPO membrane using the plastic squeeze bottle.

Colors

White and Clear

Physical Properties

Weight.....	15 lb (6.8 kg)/box
Solvents (White).....	Xylene
Solvents (Clear).....	Toluene and Xylene

Coverage Rate

100 lin ft (30.48 lin m)/bottle

Packaging

(12) 16 oz (473 ml) bottles/box

Shelf Life

Nine months when stored between 60°F (16°C) and 80°F (27°C) in unopened container.

Storage

Do not use welding or cutting torch on or near this container (even when empty). Store on shelves or pallets in a dry, climate-controlled area between 60°F (16°C) and 80°F (27°C).

Installation

Refer to JM TPO Applicator Guides or Detail Drawings for instructions.

Precautions

JM TPO Edge Sealant is extremely flammable and must be kept away from heat, sparks and flame. Use only in well-ventilated areas. Keep out of reach of children.

Refer to the Material Safety Data Sheet prior to using JM TPO Edge Sealant. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.