

Description

JM TPO Cover Tape is a 30 mil membrane with a factory-applied peel and stick adhesive tape.

Use

Use to strip in metal flanges on JM TPO Membrane systems or as directed by JM technical services.

Colors

White, Grey and Tan

Size

6" x 100' (152 mm x 30.48 m)

10" x 100' (254 mm x 30.48 m)

Physical Properties

Width6" or 10" ± ¼" (152 mm or 254 mm ± 8 mm)

Overall nominal thickness060" (1.52 mm)
(.030" [.76 mm] tape + .030" [.76 mm] TPO)

Coverage Rate

Approximately 100 ft (30.5 m) /roll

Packaging

6" (152 mm) 2 rolls/carton

10" (254 mm) 1 roll/carton

Shelf Life

Nine months when stored at temperatures between 60°F - 80°F (16°C - 27°C) in unopened containers. Elevated temperatures will shorten shelf life.

Storage

Store indoors in original unopened containers.

Do not store in direct sunlight.

Installation

1. Thoroughly mix JM TPO Membrane Primer and apply to the membrane where the JM TPO Cover Tape will be applied. Using a scrub pad and handle, apply the primer with long, continuous strokes using moderate to heavy pressure until no streaks or puddles exist.
2. Allow the primer to dry until tacky to a dry finger.
3. Center the JM TPO Cover Tape over the fasteners used to attach the metal edge. Remove the release material from the tape and apply the tape to the primed membrane surface.



4. Roll the entire length with a Teflon® or silicone rubber roller to ensure adhesion.
5. Caulk the cover tape ends, cover tape-field seam intersections and edge metal joints with JM TPO Edge Caulk.

Install JM TPO products in accordance with current JM TPO Applicator Guides or Detail Drawings.

Precautions

Refer to the Material Safety Data Sheet prior to using JM TPO Cover Tape. The Material Safety Data Sheet is available by calling (800) 922-5922 or the web at www.jm.com/roofing.