

### Description

JM TPO Detail Membrane is made from a flexible .060" (1.52 mm) nonreinforced thermoplastic polyolefin membrane. It is used for detail work such as wrapping pipes and vertical stacks and for waterproofing joints of JM TPO-Coated Metal.

### Colors

24" x 50' (61 cm x 15.24 m) - White, Grey and Tan  
 48" x 50' (122 cm x 15.24 m) - White Only

### Physical Properties

Weight . . . . . 36 lb/100 ft<sup>2</sup> (12.5 kg/m<sup>2</sup>)  
 Thickness . . . . . 0.060" (1.5 mm)  
 Roll Size . . . . . 24" or 48" x 50' (61 cm or 122 cm x 15.24 m)  
 Tear Resistance . . . . . 300 lb/in. (52.5 kN/m)

### Gross Coverage

24" x 50' (61 cm x 15.24 m) . . . . . 100 ft<sup>2</sup> (9.29 m<sup>2</sup>)  
 48" x 50' (122 cm x 15.24 m) . . . . . 200 ft<sup>2</sup> (18.58 m<sup>2</sup>)



### Storage

JM TPO Detail Membrane should be stored in a dry area protected from extreme temperatures and physical damage.

### Installation

Apply JM TPO Detail Membrane to clean, dry, smooth substrate. All surface voids more than ¼" (6.35 mm) wide must be properly filled.

Refer to JM TPO Applicator Guides or Detail Drawings for instructions.

### Precautions

**Do not install JM TPO Detail Membrane in direct contact with asphalt.**

**Refer to the Material Safety Data Sheet prior to using JM TPO Detail Membrane. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**