

## Description

JM TPO-Coated Metal is nonreinforced 20 mil (0.5 mm) JM TPO membrane laminated to 24 gauge (0.6 mm) galvanized steel. It is used as a perimeter edge metal to provide monolithic watertight protection for both adhered and mechanically fastened Johns Manville TPO Roofing Systems.

## Colors

White, Grey, Tan

## Physical Properties

Weight . . . . . 61.5 lb (27.9 kg)/sheet  
Sheet Size . . . . . 4' x 10' (1.2 m x 3.1 m)  
Thickness . . . . . 0.042" ± 0.004" (1.1 mm ± 0.1 mm)

## Packaging

(30) 4' x 10' (1.22 m x 3.05 m) sheets per pallet (approximately 630 lb [286 kg])

## Storage

JM TPO-Coated Metal must be stored flat, not on end, and protected from warping, bending or contamination. It must be kept dry and clean prior to installation.

## Installation

Refer to JM TPO Applicator Guides or Detail Drawings for instructions.

## Precautions

**Do not install JM TPO-Coated Metal in a manner where the membrane side would be in direct contact with asphalt.**

**Refer to the Material Safety Data Sheet prior to using JM TPO-Coated Metal. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).**

