

Description

JM TPO Pourable Sealer A & B is a two-part, pourable grade urethane adhesive used to seal penetrations that use penetration pockets. When mixed together, the two parts create a sealer ideal for penetration pockets. The kit contains two pails of Part A sealer and two cans of Part B along with mixing paddles.

Colors

Part A - White

Part B - Black

Physical Properties

Temperature Resistance. Continuous 200°F (93°C)
 Intermittent 220°F (104°C)
 Minimum -35°F (-37°C)

Dimensional Stability. -0.1% Length Change

Packaging

(2) 1 gal (3.79 l) pails per carton (Part A)

(2) 1 pt (0.47 l) containers (Part B)

(2) Mixing paddles (approximately 18 lb [8.17 kg])

Approximate Coverage

1 ft²/gal at 2" (5.08 mm) thick

Shelf Life

Nine months when stored between 60°F (16°C) and 80°F (27°C) in unopened container.



Storage

JM TPO Pourable Sealer must be stored in a dry area protected from weather and extreme temperatures until just prior to use.

Do not store in direct sunlight.

Installation

Pour a can of Part B sealer into the Part A pail. Mix thoroughly with the provided paddles. Continue mixing until sealer becomes completely black. Do not thin. Pour the sealer into a clean, dry penetration pocket. Only mix the amount of sealer that will be used within the next hour. Pourable sealer is a maintenance item and is not covered by the guarantee.

Refer to JM TPO Applicator Guides or Detail Drawings for instructions.

Precautions

Use only in well-ventilated areas. Close container after use to protect from moisture. Keep out of reach of children and avoid contact with skin. Do not apply below 40°F (4°C) or when surface temperature is less than 5°F (3°C) above the dew point.

Refer to the Material Safety Data Sheet prior to using JM TPO Pourable Sealer A & B. Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.