

Description

JM TPO Walkpad is a $\frac{5}{32}$ " (3.97 mm) thick, textured thermoplastic sheet.

Use

Use to protect the roofing membrane system in high rooftop traffic areas such as rooftop units that require regular maintenance.

Color

Grey

Physical Properties

Weight/roll96 lb (43.54 kg)
 Thickness $\frac{5}{32}$ " (3.97 mm)
 Roll Size 30" x 50' (76.2 cm x 15.24 m)

Gross Coverage

125 ft² (11.61 m²) per roll

Packaging

30" x 50' (76.2 cm x 15.24 m) roll

Storage

Store in a dry area protected from extreme temperatures and physical damage.

Installation

Heat weld the JM TPO Walkpad to the JM TPO Membrane. Install textured side up over the membrane with a 2" (5.08 cm) continuous weld around the sheet perimeter to ensure water tightness.

Keep all pads at least 2" (5.08 cm) from field-fabricated seams, around penetrations and adjacent walkpads. To allow for proper drainage, ensure the walkpad is no longer than 10 feet (3.05 m) when installed.

Install JM TPO products in accordance with current JM TPO Applicator Guides or Detail Drawings.



Energy and the Environment

LEED®	Recycled Content
	Postconsumer: 0% Postindustrial: 55%
	Producing Locations
	Chelsea, MA

Precautions

When installing JM TPO Walkpads be sure to:

- Achieve a full weld around the perimeter of the material.
- Install textured side up.
- Minimize installing over seams and membrane splices whenever possible.
- On mechanically fastened systems, avoid installing over the disc.

Refer to the Material Safety Data Sheet prior to using JM TPO Walkpads. Material Data Safety Sheet is available by calling (800) 922-5922 or the Web at www.specjm.com/roofing.