








SBS Hot Asphalt-Applied and Cold Adhesive-Applied Modified Bitumen Membrane Selector Guide

Product	Use					Reinforcement			Application					ASTM	Size
	Base	Ply	Cap	Flashing	Protection	Fiber Glass	Polyester	Composite	Hot Asphalt 	Cold Adhesive 	Heat Weld 	Self-Adhering 	Mechanically Fastened 		
DynaBase®	X					X			X	X				D 6163, Type I, Grade S	150 ft ² (13.94 m ²)
DynaClad®				X		X			X	X				D 6298	100 ft ² (9.29 m ²)
DynaClad® Copper				X		X			X	X				D 6298	100 ft ² (9.29 m ²)
DynaGlas®			X			X			X	X				D 6163 Type I, Grade G	100 ft ² (9.29 m ²)
DynaGlas® FR			X			X			X	X				D 6163 Type I, Grade G	100 ft ² (9.29 m ²)
DynaGlas® FR CR			X			X			X	X				D 6163 Type I, Grade G	100 ft ² (9.29 m ²)
DynaGlas® 30 FR			X			X			X	X				D 6163 Type I, Grade G	100 ft ² (9.29 m ²)
DynaLastic® 180 S	X						X		X	X			X	D 6164 Type I, Grade S	100 ft ² (9.29 m ²)
DynaBase® PR	X						X		X	X			X	D 6164 Type I, Grade S	150 ft ² (13.94 m ²)
DynaLastic® 180			X				X		X	X				D 6164 Type I, Grade G	100 ft ² (9.29 m ²)
DynaLastic® 180 FR			X				X		X	X				D 6164 Type I, Grade G	100 ft ² (9.29 m ²)
DynaLastic® 180 FR CR			X				X		X	X				D 6164 Type I, Grade G	100 ft ² (9.29 m ²)
DynaLastic® 250			X				X		X	X				D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaLastic® 250 FR			X				X		X	X				D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaLastic® 250 FR CR			X				X		X	X				D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaPly®	X							X	X	X				D 6162 Type II, Grade S	100 ft ² (9.29 m ²)
DynaFlex®				X				X	X	X				D 6221 Type I	75 ft ² (6.98 m ²)
DynaFlex® CR				X				X	X	X				D 6221 Type I	75 ft ² (6.98 m ²)
DynaKap®			X					X	X	X				D 6162 Type II, Grade G	100 ft ² (9.29 m ²)
DynaKap® FRO			X					X	X	X				D 6162 Type II, Grade G	100 ft ² (9.29 m ²)
DynaKap® FR CR			X					X	X	X				D 6162 Type II, Grade G	100 ft ² (9.29 m ²)
DynaTred™					X				X	X				NA	
DynaTred™ Plus					X				X	X				NA	