








SBS Heat Weldable Modified Bitumen Membrane Selector Guide

Product	Use					Reinforcement			Application					ASTM	Size
	Base	Ply	Cap	Flashing	Protection	Fiber Glass	Polyester	Composite	Hot Asphalt 	Cold Adhesive 	Heat Weld 	Self-Adhering 	Mechanically Fastened 		
DynaBase® HW	X					X					X			D 6163, Type I, Grade S	150 ft ² (13.94 m ²)
DynaWeld™ Base	X					X					X			D 6163, Type I, Grade S	100 ft ² (9.29 m ²)
DynaWeld™ Cap			X			X					X			D 6163, Type I, Grade G	100 ft ² (9.29 m ²)
DynaWeld™ Cap FR			X			X					X			D 6163, Type I, Grade G	100 ft ² (9.29 m ²)
DynaWeld™ Cap FR CR			X			X					X			D 6163, Type I, Grade G	100 ft ² (9.29 m ²)
DynaWeld™ 180 S	X						X				X		X	D 6164 Type I, Grade S	100 ft ² (9.29 m ²)
DynaWeld™ 250 S	X						X				X		X	D 6164 Type II, Grade S	100 ft ² (9.29 m ²)
DynaWeld™ Cap 180 FR			X				X				X			D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaWeld™ Cap 180 FR CR			X				X				X			D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaWeld™ Cap 250 FR			X				X				X			D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaWeld™ Cap 250 FR CR			X				X				X			D 6164 Type II, Grade G	100 ft ² (9.29 m ²)
DynaPly® HW	X							X			X			D 6162 Type II, Grade S	100 ft ² (9.29 m ²)
DynaKap® FR HW			X					X			X			D 6162 Type II, Grade G	100 ft ² (9.29 m ²)