








SBS Self-Adhering Modified Bitumen Membrane Selector Guide

Product	Use					Reinforcement			Application					ASTM	Size
	Base	Ply	Cap	Flashing	Protection	Fiber Glass	Polyester	Composite	Hot Asphalt 	Cold Adhesive 	Heat Weld 	Self-Adhering 	Mechanically Fastened 		
DynaGrip™ Base SA/SA	X					X						X		D 5147	200 ft ² (18.58 m ²)
DynaGrip™ Base SD/SA	X					X						X		D 5147	200 ft ² (18.58 m ²)
DynaGrip™ Cap			X			X						X		D 5147	100 ft ² (9.29 m ²)
DeckPro™	X					X							X	D 5147	700 ft ² (64.5 m ²)
JM CleanBond® SBS Base	X					X						X		D 5147	200 ft ² (18.58 m ²)
JM CleanBond® Utility Sheet	X					X						X		D 6163	100 ft ² (9.29 m ²)
JM CleanBond® Cap			X			X						X		D 6163 Type I, Grade G	100 ft ² (9.29 m ²)
JM CleanBond SBS Base Flashing				X			X					X		D 5147	100 ft ² (9.29 m ²)
JM CleanBond Cap Flashing				X			X					X		D 5147	75 ft ² (6.98 m ²)