



UltraLok™ Locking Impact Fastener and Plate

Description

UltraLok Locking Impact Fasteners and Plates consist of a pre-assembled Galvalume®*-coated steel tube, a 2.7" (6.86 cm) Galvalume-coated steel disc, and a precision-formed, coated-steel, high tensile, wire-locking staple. The disc is securely clamped to the tube and is rib-reinforced to resist cupping.

Use

Attach base sheets and cover boards to poured gypsum, cementitious wood fiber and lightweight concrete decks. The UltraLok fastener cannot be used for insulation, nor can it be used to mechanically attach single ply. The pre-assembled unit provides positive attachment and resistance to uplift forces.

UltraLok fasteners are approved to secure JM base ply sheets within any Peak Advantage® Guarantee.

Advantages

- Greatly reduces installation time and labor costs.
- Shaped to easily penetrate decking and membrane.
- Galvanized-coating resists corrosion.
- UltraLok disc prevents fastener pop-up.
- UltraLok fasteners are FM Global and Miami-Dade County Product Control Approved.



Sizes and Packaging

1.4" (3.6 cm) length	500/carton
1.8" (4.6 cm) length	500/carton
2.8" (7.1 cm) length	500/carton
3.8" (9.6 cm) length	500/carton
4.8" (12.2 cm) length	250/carton

Precautions

Refer to the Material Safety Data Sheet prior to using UltraLok Locking Impact Fasteners and Plates. The Material Safety Data Sheet is available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.

*Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.